

2014+ FORD FIESTA ST TRUNK BRACE

PARTS LIST AND INSTALLATION GUIDE



PARTS LIST

1 PC | STEEL TRUNK BRACE

1 PC | FALSE-FLOOR MOUNTING TABS

MOUNTING HARDWARE

TOOLS NEEDED

8MM SOCKET

T50 TORX SOCKET

1/4" EXTENSION

3/8" EXTENSION

1/4" DRIVE RATCHET

3/8" DRIVE RATCHET

INSTALLATION TIME **UNDER .5 HOUR**

INSTALL DIFFICULTY

DISCLAIMER

- Raise vehicle only on jack stands or on a vehicle lift.
- Allow vehicle to cool completely prior to attempting installation.
- Do not run the engine or drive the vehicle while overheating; serious damage can occur.
- Please dispose of any liquids properly.
- Mishimoto is not responsible for any vehicle damage or personal injury due to installation errors, misuse, or removal of Mishimoto products.
- Mishimoto suggests that a trained professional install all Mishimoto products.

INSTALLATION INSTRUCTIONS

01. Remove the false floor from the trunk of the vehicle.

02. Remove the two bolts that secure the false-floor mounts to the vehicle. Then remove the false-floor mounts. Note the location of the mounting pins and clip on the back of the mounts for reinstallation. (2x 8mm bolts)



03. Remove the two bolts that secure the outer seat mounts. (2x T50 Torx bolts)



04. Lower the Mishimoto strut brace into place over the seat mounts. Secure the strut brace and the seat mounts using the hardware you just removed. (2x T50 Torx bolts)



05. Reinstall the false-floor mounts, and secure them with the original hardware. (2x 8mm bolts)

06. To support the false floor in its lower position, install the false floor and slip the mounting brackets underneath it. Align the holes in the brackets with the threaded holes on the trunk brace, and secure the brackets with the two thumbscrews. (2x mounting brackets, 2x thumbscrews)



Congrats! You just finished installing the 2014+ Ford Fiesta ST Trunk Brace.

01